


# Pneumatic Pumps

## SIDEWINDER PUMP MODEL NUMBER CHART

*Fill in boxes below to determine Sidewinder Pump Size and Material Requirements*



### Plunger Size

04	0.250"
06	0.375"
08	0.500"
16	1.000"

### Check Valve & Body Material

316 SS (Standard)	2
Hastelloy	5
Titanium	6

### Production Series\*

Piston Size	Series*
0	1.25" F, G, H
2	2.25" C, D, F
4	4.00" C, D

### Plunger Packing

0	Teflon Graphite Uniseal
1	Techno Uniseal (Polyimede)
2	Viton O-ring
3	Buna O-ring
4	Teflon Uniseal
4B	Teflon Uniseal w/Buna O-ring Insert
4V	Teflon Uniseal w/Viton O-ring Insert
5	Chemraz O-ring
6	Hitec O-ring (Aflas)
7	Virgin Teflon O-ring
8	Polyblend Uniseal
9	Special
V	Teflon Graphite Uniseal w/ Viton O-ring Insert

### Plunger Material

0	17-4 SS (Standard)
2	316 SS
3	440C SS
4	Ceramic
5	Hastelloy
6	Titanium
7	Chrome Plated Stainless Steel
8	Electroless Nickel Plated Stainless Steel

### Special Options

- 2-Viton Piston U-Cup
- 4-Ceramic Check Valve Balls
- MP-Ni Cobalt Moly Return Spring
- GS-Gas Recovery Model (42D/62F/82D only)

\*Production Series designates current factory production model.  
For explanation of production series, visit our website.