

PLUNGER PUMP SPECIFICATIONS

Series Number	40	42	44	44CR	60	62	64	64CR	80	82	84	84CR	164	164CR
Plunger Size	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	1"	1"
Piston Size	1.25"	2.25"	4"	4"	1.25"	2.25"	4"	4"	1.25"	2.25"	4"	4"	4"	4"
Amplification Ratio	25:1	80:1	240:1	240:1	11:1	36:1	110:1	110:1	6.25:1	20:1	60:1	60:1	16:1	16:1
Supply Pressure (PSI)	15 to 150	10 to 150	10 to 45	10 to 45	15 to 150	10 to 150	10 to 95	10 to 95	15 to 150	10 to 150	10 to 150	10 to 150	10 to 150	10 to 150
Discharge Pressure (PSI)	0 to 3,500	0 to 10,000	0 to 10,000	0 to 10,000	0 to 1,600	0 to 5,400	0 to 10,000	0 to 10,000	0 to 935	0 to 3,000	0 to 9,000	0 to 9,000	0 to 2,400	0 to 2,400
Full Strokes/Minute (Max.)	60	55	35	55	60	55	30	55	60	55	30	35	40	55
Output Volume (QPD)	0 to 90	0 to 70	0 to 30	0 to 50	0 to 200	0 to 155	0 to 67	0 to 122	0 to 360	0 to 275	0 to 120	0 to 220	0 to 680	0 to 935
Suction-Discharge Size (MNPT_FNPT)	1/4"-1/4"	1/4"-1/4"	1/4"-1/4"	1/4"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	1/2"-1/4"	3/4"-1/2"	3/4"-1/2"

WALKING BEAM PUMP SPECIFICATIONS

Model Number	WB-4	WB-8
Plunger Size	1/4"	1/2"
Discharge Pressure (PSI)	0-3,000	0-1,000
Maximum Output (QPD)	Strokes/Min. x 1	Strokes/Min. x 4
Inlet Connection	1/4" MNPT	1/2" MNPT
Outlet Connection	1/4" MNPT	1/4" MNPT